

Technical Data Sheet

V 1.0 Dec. 2016

Solid Acrylic Resin PChem[®] GA-030

- 1. GA-030 is a solid acrylic resin that is designed for use in overprint varnishes and flexographic and gravure-printing inks.
- 2. GA-030 has the following characteristics and performance features:
- · Gloss improvement
- Increase of transfer and resolubility
- · Improvement of heat and blocking resistance
- · free of glycols and glycol ethers
- 3. Technical Data

Property	Value	Unit	Test method
Appearance	clear granules	NA	NA
Glass transition temperature (Tg)	appr.82	°C	ASTM D-3418
Inherent viscosity (IV)	0.06±0.01	dL/g	ASTM D-2857
Acid value	240-260	mg KOH/g	ISO-3682
Non-volatile	≥ 99	%	ASTM D-1259

Packaging and recommended storage conditions

- 1. Packed in composite paper bag with inner plastic bag, 25kg net.
- 2. Store in cool, dry and ventilated place where the fire and organic solvents are prohibited.
- 3. Shelf life: 2 years if storage in cool dry location below 32°C, capable of further use after passing QC inspection.

4, Transport as non-dangerous material.

Notes: The information contained on above data sheet is, to the best of our current knowledge, true and accurate. However, since the conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liabilities in connection with the use of information contained herein or otherwise. All risks of such nature are assumed by the user.

Shanghai Pioneer Chemicals Co., Ltd.www.sh-pioneer.com.cnTel: 021-599514845F Jinyuan Building, 1218 Yongsheng Road, Jiading district,
Shanghai 201821, Chinaemail: 9long@9long.com.cnFax: 021-59951794